



STYLE
7200R / 7250R

RESIDENTIAL

7200R - BLACKOUT FABRIC
7250R - LIGHT-FILTERING FABRIC

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 7200R - BLACKOUT							
RB1	Swan	0	71	29	0	0.23	0.19
RB8	Raven	0	70	30	0	0.23	0.20



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



MIF Seal of Approval



TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at www.phifer.com.



STYLE
7200R

RB1
Swan

RB2
Oyster

RB3
Sail

RB4
Chiffon

RB6
Earl Grey

RB5
Chrome

RB7
Blazer

RB8
Raven



STYLE
7250R

RL1
Swan

RL2
Oyster

RL3
Sail

RL4
Chiffon

RL6
Earl Grey

RL5
Chrome

RL7
Blazer

RL8
Raven

STYLE 7200R / 7250R SPECIFICATIONS

Whether contemporary or traditional, Style 7200R complements any design scheme, combining total light blockage with a neutral yet subtly variegated pattern. Style 7250R offers a light-filtering option, using the same face fabric and pattern of Style 7200R to allow natural light to brighten interior spaces.

These fabrics are suitable for roller shades, Roman shades and panel track systems and are ideal for residential use.

STYLE 7200R FIRE CLASSIFICATION California Technical Bulletin 117 IBC Section 803.1.1 (Class B Rating)
NFPA 101 (Class B Rating)

STYLE 7250R FIRE CLASSIFICATION California Technical Bulletin 117 IBC Section 803.1.1 (Class A Rating)
NFPA 101 (Class A Rating)

Fire classifications are subject to change. Please go to phifer.com for the most current information.

BACTERIA AND FUNGAL RESISTANCE ASTM G21-96 AATCC 174-1998 Part II and III

ENVIRONMENTAL CERTIFICATION GREENGUARD GREENGUARD Gold
Certified to these standards for low chemical emissions into indoor air during product usage

SAFE USE RoHS/Directive 2002/95/EC
ANSI/WCMA A 100.1-2007 for lead content
US Consumer Product Safety Commission Section 101

WARRANTY 5-year interior

UV PROTECTION Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

CLEANING INSTRUCTIONS Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

Railroading this fabric is not recommended.

Colors may vary slightly from swatch samples. All variations are within industry standards.

STYLE	7200R	7250R
WIDTHS	118" 300 cm	118" 300 cm
ROLL LENGTH	22 Linear Yards 20 Linear Meters	22 Linear Yards 20 Linear Meters
COMPOSITION	100% Polyester with Acrylic Foamed Backing	100% Polyester with Acrylic Coating
MESH WEIGHT	11.06 oz/yd ² 375 g/m ²	6.19 oz/yd ² 210 g/m ²
FABRIC THICKNESS	0.024 in 0.60 mm	0.018 in 0.45 mm
OPENNESS FACTOR	Opaque	Light-filtering

PHIFER
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403 -1700 USA
Phone: 205.345.2120 • FAX: 205.391.0799
Toll Free USA/Canada: 1.800.221.5497
phifer.com • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.
™ UL, the UL logos and the UL mark are trademarks of UL LLC.
Photo courtesy of Hunter Douglas, South America.
© PHIFER INCORPORATED V20 021420 3038201