



STYLE  
7700R / 7750R

RESIDENTIAL

7700R - BLACKOUT FABRIC  
7750R - LIGHT-FILTERING FABRIC

---

WEAVING  
EXCELLENCE  
WITH  
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
<b>STYLE 7700R - BLACKOUT</b>							
TB1	Crystal	0	70	30	0	0.24	0.19
TB2	Sand	0	57	43	0	0.31	0.23
TB3	Concrete	0	44	56	0	0.38	0.27
TB4	Chalk	0	59	41	0	0.30	0.23
TB5	Graphite	0	44	56	0	0.38	0.26
TB6	Pewter	0	22	78	0	0.50	0.32
TB7	Onyx	0	6	94	0	0.58	0.37



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorptance  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values, test  
references and technical definitions visit us at  
phifer.com.



STYLE  
7700R

TB1  
**Crystal**

TB4  
**Chalk**

TB3  
**Concrete**

TB2  
**Sand**

TB5  
**Graphite**

TB6  
**Pewter**

TB7  
**Onyx**



STYLE  
7750R

TL1  
**Crystal**

TL4  
**Chalk**

TL3  
**Concrete**

TL2  
**Sand**

TL5  
**Graphite**

TL6  
**Pewter**

TL7  
**Onyx**



# STYLE 7700R / 7750R SPECIFICATIONS

Featuring a soft, textured pattern evoking the look of grasscloth, Style 7700R offers a PVC-free blackout option for total light blockage. Style 7750R filters natural light while maintaining the look of the face fabric of Style 7700R. A color-coordinated backing ensures the same neutral fabric color is shown toward both the interior of the room and glass.

These fabrics are suitable for roller shades, Roman shades and panel track systems and are ideal for residential use.

**STYLE 7700R FIRE CLASSIFICATION** California Technical Bulletin 117

**STYLE 7750R FIRE CLASSIFICATION** California Technical Bulletin 117 IBC Section 803.1.1 (Class A Rating)  
NFPA 101 (Class A Rating)

*Fire classifications are subject to change. Please go to [phifer.com](http://phifer.com) for the most current information.*

**BACTERIA AND FUNGAL RESISTANCE** ASTM G21-96 AATCC 174-1998 Part II and III

**ENVIRONMENTAL CERTIFICATION** GREENGUARD GREENGUARD Gold  
Certified to these standards for low chemical emissions into indoor air during product usage

**SAFE USE** RoHS/Directive 2002/95/EC  
ANSI/WCMA A 100.1-2007 for lead content  
US Consumer Product Safety Commission Section 101

**WARRANTY** 5-year interior

**UV PROTECTION** Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

**CLEANING INSTRUCTIONS** Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

*Railroading this fabric is not recommended.  
Colors may vary slightly from swatch samples. All variations are within industry standards.*

STYLE	7700R	7750R
<b>WIDTHS</b>	118" 300 cm	118" 300 cm
<b>ROLL LENGTH</b>	22 Linear Yards 20 Linear Meters	22 Linear Yards 20 Linear Meters
<b>COMPOSITION</b>	100% Polyester with Acrylic Foamed Backing	100% Polyester with Acrylic Coating
<b>MESH WEIGHT</b>	13.6 oz/yd <sup>2</sup> 461 g/m <sup>2</sup>	8.8 oz/yd <sup>2</sup> 298 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.028 in 0.71 mm	0.023 in 0.58 mm
<b>OPENNESS FACTOR</b>	Opaque	Light-filtering

**PHIFER**  
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403 -1700 USA  
Phone: 205.345.2120 • FAX: 205.391.0799  
Toll Free USA/Canada: 1.800.221.5497  
[phifer.com](http://phifer.com) • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
™ UL, the UL logos and the UL mark are trademarks of UL LLC.  
Photo courtesy of Hunter Douglas, South America.  
© PHIFER INCORPORATED V20 021420 3038202